



Concrete Protection & Repair Products, Inc.

1315 West Lark Industrial Park Drive

Saint Louis, Missouri 63026

Phone: (636) 717-0666 Toll Free: 888-531-8940

www.cpr-products.com

MATERIAL SAFETY DATA SHEET

Prepared January 2014 Complies with OSHA Hazard Communication Standard 29 CFR 1910.1200

SECTION 1: PRODUCT INFORMATION

PRODUCT NAME: **SURFACE SLICK**

PRODUCT NUMBER: **SURFACE SLICK**

PRODUCT CLASS: **WATER BASED LUBRICANT**

SECTION 2: HAZARDOUS INGREDIENTS

NO HAZARDOUS INGREDIENTS ABOVE REPORTABLE LEVELS

NON-HARZARDOUS / NON-TOXIC

SECTION 3: PHYSICAL DATA

BOILING RANGE: **> 212 deg. F** VAPOR DENSITY: **HEAVIER THAN AIR** EVAPORATION RATE: **= TO WATER**

VOLATILE BY VOLUME: **0%**

WEIGHT/GAL: **7.5 - 8.5 LBS**

SECTION 4: FIRE AND EXPLOSION DATA

FLAMMABILITY: **NON-FLAMMABLE, NON-COMBUSTIBLE** FLASH POINT: **> 230 deg. F**

EXTINGUISHING MEDIA: **FOAM, CO2, DRY CHEMICAL, WATER** UNUSUAL FIRE HAZARDS: **NONE**

FIREFIGHTING PROCEDURE: **WEAR FULL-FACE SELF-CONTAINED BREATHING APPARATUS AND USE WATER FOG NOZZLES TO COOL CLOSED CONTAINERS**

SECTION 5: HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE ----- EMERGENCY FIRST AID PROCEDURES

EYES: May cause slight irritation ----- Flush with water 15 minutes. Seek medical attention

SKIN: May cause slight irritation ----- Remove contaminated clothing. Wash affected area with soap and water

INHALATION: May cause slight irritation ----- Move to fresh air. Seek medical attention if necessary

INGESTION: Consult physician. Do not take internally ----- Induce vomiting. Seek immediate medical attention

SECTION 6: REACTIVITY DATA

STABILITY: **STABLE** CONDITIONS TO AVOID: **EXCESSIVE HEAT**

HAZARDOUS DECOMPOSITION PRODUCTS: **BURNING CAN CAUSE CO₂ AND CO**

HAZARDOUS POLYMERIZATION: **WILL NOT OCCUR**

INCOMPATIBILITY: **MATERIALS CONTAINING PHOSPHORUS OR OXIDIZERS**

SECTION 7: SPILL OR LEAK PROCEDURE

STEPS TO TAKE IF MATERIAL IS RELEASED OR SPILLED: **VENTILATE AREA. ABSORB SPILL WITH SUITABLE ABSORBANT MATERIAL AND PLACE IN CLOSED CONTAINER. PREVENT MATERIAL FROM ENTERING WATERWAYS.**

WASTE DISPOSAL METHOD: **MATERIAL MAY BE DEPOSITED IN A LANDFILL IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS**

SECTION 8: SAFE HANDLING & USE INFORMATION

RESPIRATORY PROTECTION: **IF TLV OF PRODUCT OR ANY COMPONENT IS EXCEEDED, A NIOSH/MSHA JOINTLY APPROVED AIR-SUPPLIED RESPIRATOR IS ADVISED IN THE ABSENCE OF PROPER ENVIRONMENTAL CONTROL**

VENTILATION: **PROVIDE SUFFICIENT MECHANICAL VENTILATION TO MAINTAIN EXPOSURE BELOW TLV**

PROTECTIVE CLOTHING: **IMPERVIOUS GOGGLES, GLOVES, AND CLOTHING PREVENT EYE AND SKIN CONTACT**

HYGIENIC PRACTICES: **WASH WITH SOAP AND WATER AFTER USE AND BEFORE EATING OR SMOKING**

SECTION 9: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: **STORE IN DRY AREA. KEEP CONTAINERS TIGHTLY CLOSED. PROTECT FROM PHYSICAL DAMAGE. EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES - ALL HAZARD PRECAUTIONS GIVEN IN DATA SHEET MUST BE OBSERVED. STORE BELOW 120 deg. F**

OTHER PRECAUTIONS: **KEEP FROM FREEZING. FROZEN MATERIAL MAY EXPAND AND CAUSE RUPTURE OF CONTAINER**

WARRANTY: The information contained in this document is to assist customers in determining whether our products are suitable for their applications. Our products are intended for sale to industrial and commercial customers. The customer must inspect and test our products before use, and satisfy themselves as to the contents and suitability. Nothing herein shall constitute a warranty, expressed or implied, including any warranty of merchantability or fitness, nor is protection from any law or patent to be inferred. All patent rights are reserved. The exclusive remedy for all proven claims is replacement of our materials, and in no event shall we be liable for special, incidental, or consequential damages.